

Wall-Mounted Type CTXM-R Series

				Reverse cycle			
Model name				CTXM20RVMA	CTXM25RVMA	CTXM35RVMA	CTXM46RVMA
Power supply				1 phase, 220-240 V, 50 Hz / 1 phase, 220-230 V, 60 Hz			
Front panel colour				White			
Indoor airflow rate	H	Cooling	l/s (cfm)	155 (328)	173 (367)	188 (399)	203 (431)
		Heating		160 (339)	173 (367)	188 (399)	202 (427)
Indoor sound pressure level	H/L/SL	Cooling	dB(A)	38/25/19	40/25/19	42/26/19	44/35/26
		Heating		39/28/20	40/28/20	42/29/20	43/33/26
Indoor sound power level	H	Cooling	dB(A)	52	54	56	58
		Heating		53	54	56	57
Fan speed				5 steps, quiet and automatic			
Temperature control				Microcomputer control			
Dimensions	H x W x D		mm	285 x 770 x 223			
Machine weight			kg	9			
Piping connections	Liquid (flare)		mm	ø6.4			
	Gas (flare)			ø9.5		ø12.7	
	Drain			ø16.0			
Heat insulation				Both liquid and gas pipes			

				Reverse cycle				
Model name				CTXM50RVMA	CTXM60RVMA	CTXM71RVMA	CTXM85RVMA	CTXM95RVMA
Power supply				1 phase, 220-240 V, 50 Hz / 1 phase, 220-230 V, 60 Hz				
Front panel colour				White				
Indoor airflow rate	H	Cooling	l/s (cfm)	282 (597)	325 (689)	333 (706)	398 (844)	400 (848)
		Heating		287 (607)	333 (706)	328 (696)	422 (893)	413 (876)
Indoor sound pressure level	H/L/SL	Cooling	dB(A)	45/35/28	48/36/29	49/37/30	51/40/37	53/42/38
		Heating		45/33/28	48/33/29	49/35/30	51/38/35	52/38/35
Indoor sound power level	H	Cooling	dB(A)	59	62	63	65	67
		Heating		59	62	63	65	66
Fan speed				5 steps, quiet and automatic				
Temperature control				Microcomputer control				
Dimensions	H x W x D		mm	295 x 990 x 263			340 x 1,200 x 259	
Machine weight			kg	13			17	18
Piping connections	Liquid (flare)		mm	ø6.4				
	Gas (flare)			ø12.7		ø15.9		
	Drain			ø16.0				
Heat insulation				Both liquid and gas pipes				